























































Standard Screws, Drill Bits and Taps

Screw Diameter (mm)											
Thread Diameter	1.5		2.0		2.4		2.7	3.5	4.0		
Screw Type	Cortical								Cancellous		
									Fully Threaded	Partially Threaded	Fat Neck Fully Threaded
Self-Tapping	✓	✓	✓	✓	✓	✓	✓	✓			
Non-Self-Tapping	✓		✓				✓	✓	✓	✓	✓
Drill Bit and Tap Diameter (mm)											
Drill Bit for Gliding Hole	1.5	1.5	2.0	2.0	2.4	2.4	2.7	3.5	-	-	-
											
											
Drill Bit for Threaded Hole	1.1	1.1	1.5	1.5	1.8	1.8	2.0	2.5	2.0		
Tap Part Number	1.5 001906	1.5 001906	2.0 001907	2.0 001907	-	-	2.7 001908	3.5 001909	4.0 001911		
Drive Type	1.5/2.0mm Cruciform	1.5mm Hexagonal	1.5/2.0mm Cruciform	1.5mm Hexagonal	2.4mm Cruciform	2.0mm Hexagonal	2.5mm Hexagonal	2.5mm Hexagonal	2.5mm Hexagonal		

Standard Screws, Drill Bits and Taps

Screw Diameter (mm)											
Thread Diameter	1.5		2.0		2.4		2.7	3.5	4.0		
Screw Type	Cortical								Cancellous		
									Fully Threaded	Partially Threaded	Fat Neck Fully Threaded
Self-Tapping	✓	✓	✓	✓	✓	✓	✓	✓			
Non-Self-Tapping									✓	✓	✓
Drill Bit and Tap Diameter (mm)											
Drill Bit for Gliding Hole	1.5	1.5	2.0	2.0	2.4	2.4	2.7	3.5	-	-	-
											
											
Drill Bit for Threaded Hole	1.1	1.1	1.5	1.5	1.8	1.8	2.0	2.5	2.0		
Tap Part Number	1.5 001906	1.5 001906	2.0 001907	2.0 001907	-	-	2.7 001908	3.5 001909	4.0 001911		
Drive Type	1.5/2.0mm Cruciform	1.5mm Hexagonal	1.5/2.0mm Cruciform	1.5mm Hexagonal	2.4mm Cruciform	2.0mm Hexagonal	2.5mm Hexagonal	2.5mm Hexagonal	2.5mm Hexagonal		

Smooth and Spiked Washers







Smooth Washers					
Part Number	002446	002444	002445	003655	003656
					
Outside Diameter (mm)	4.5	6.5	7.0	10	13
Inside Diameter (mm)	2.2	2.8	4.0	5.2	6.7
Thickness (mm)	0.6	0.9	0.9	1	0.9
For Use With Screw Sizes	1.5mm, 2.0mm	2.4mm, 2.7mm	2.7mm, 3.5mm	4.0mm, 4.5mm	4.5mm, 5.5mm, 6.5mm
Spiked Washers					
Part Number	001884	002607	002441	001656	002442
					
Outside Diameter (mm)	8	8	13	11	13
Inside Diameter (mm)	3.2	3.6	4.3	4.6	6.7
Thickness (mm)	4	4	4	3.4	3.8
For Use With Screw Sizes	2.0mm, 2.4mm	2.4mm, 2.7mm	2.7mm, 3.5mm	3.5mm, 4.0mm	4.5mm, 5.5mm, 6.5mm

Securos Surgical USA
443 Main St.
Fiskdale, MA 01518
Tel: 1 (877) BONEFIX (266-3349)
Fax: (508) 347-5330
info@securos.com
www.securos.com

Securos Surgical Europe GmbH
Take Off Gewerbepark
Newhausen Ob Eck Germany
Tel: +49 7467 9476 50
Fax: +49 7467 9476 52
info@securos-europe.eu
www.securos-europe.eu

Securos Surgical UK
4Admail 4017
Coventry, CV1 1YS England
Tel: +0845 070 2498
Fax: +0845 070 2499
sales@securos.co.uk
www.securos.co.uk

Standard Screws, Drill Bits and Taps

Screw Diameter (mm)					
Thread Diameter	4.5	5.5	6.5		
Screw Type	Cortical		Cancellous		
			Fully Threaded	32mm Thread Length	16mm Thread Length
Self-Tapping	✓				
Non-Self-Tapping		✓	✓	✓	
Drill Bit and Tap Diameter (mm)					
Drill Bit for Gliding Hole	4.5	5.5	4.5		
					
	Drill Bit for Threaded Hole	3.2	4.0	3.2	
Tap Part Number	4.5 001910	5.5 002500	6.5 002503		
Drive Type	3.5mm Hexagonal	3.5mm Hexagonal	3.5mm Hexagonal		